



**Finish:** Gloss

**Format:** Panel

**Thickness:** 18mm

**With Film**

**Length:** 2.850mm

**Width:** 1.220mm



FEATURE	STANDARD	CRYSTAL
COVERING ADHESION (% particles dragging)	UNE EN ISO 2409:2013	1--2
CRACK RESISTANCE	UNE EN 14323:04	5
SURFACE SOUNDNESS	UNE EN 311:2002	1,2 N/mm <sup>2</sup>
COLD CHECK 30 CYCLES (INITIAL TEMP. 60°)	UNE 48 025:1979	No damage
LIGHT FASTNESS	UNE EN 14323:04	E. grey 4-5
BEHAVIOUR AGAINST DRY HEAT	UNE EN 12722:09+A1:14	5
BEHAVIOUR IMPACT STRESS (LARGE DIAMETER STEEL BALL)	UNE EN 14323:04	200 cm
CHEMICAL STRESS (food, drinks, cleaning products, etc.)	DIN 68 861-1:11	1C
RESISTANCE TO COLD LIQUIDS (coffee, ethanol, sodium carbonate, sodium chloride, tea)	UNE EN 12720:09+A1:14	5
BEHAVIOUR OF MOIST HEAT	UNE EN 12721:09+A1:14	5
BEHAVIOUR AGAINST SCRATCHING	UNE EN 15186:12 (lineal method)	20 N (tread width 0,13mm)
BEHAVIOUR AGAINST CIGARETTE BURNS	UNE EN 14323:04	2
BEHAVIOUR AGAINST WATER VAPOUR	UNE EN 14323:04	4
20 DEGREE GLOSS	UNE EN 14323:04	90 ± 5 GU



TRANSFORMAD QUALITY

01/01/2015

VERSION 1.0