

IBAITI MILL

Declaration of Performance No. SUI/PP/13/CE4

 ϵ

Product identification	PINE PLYWOOD EN 636-2 G							
Product Types	8mm	9mm	12mm	15mm	18mm	21mm	24mm	27mm
Intended uses	Internal use as non-structural components in humid conditions							

Name and contact address	Indústria de Compensados Sudati Ltda.			
of the manufacturer	Rod. BR 153, Km 04, s/n			
	Ibaiti, PR 84900-000 BRAZIL			
Mill identification	SUDATI - IBAITI			
Harmonized standard	EN 13986:2004			
AVCP System	4			

Essential characteristics	Declared performance	Technical Specification
Release of formaldehyde	E1 (phenolic resin bonded)	EN 13986 Annex B Note 2
Bond quality	Class 3	EN 314-1/2 Type testing
Density	580 Kg/m3	EN 323 Type testing
Water vapour permeability	Wet - 70 μ / Dry - 200 μ	EN 13986 Table 9
Airborne sound insulation	R = 13 x lg (m _A) + 14	EN 13986 part 5.10
Sound absorption coefficient	0,10 / 0,30	EN 13986 Table 10
Thermal conductivity	0,13 W/(m.K)	EN 13986 Table 11
Content of pentachlorophenol	< 5 ppm	EN 13986 part 5.18

Dimensional t	tolerances	Declared performance				Technical Specification			
Length and w	vidth	+0 / -3.0mm							
Squareness		+/- 1.0 mm/m			EN 324-2				
Straigthness		+/- 1.0 mm/m			7				
		See below per Type			EN 324	-1 / EN 31	L5 / EN 12	871	
Thickness	Product Type	8mm	9mm	12mm	15mm	18mm	21mm	24mm	27mm
THICKNESS	Maximum (mm)	8,9	8,9 10,1 13,2 16,3		16,3	19,3	22,4	25,5	28,6
	Minimum (mm)	7,4	8,3	11,2	14,2	17,1	20,0	22,9	25,8

Essential characteristics		Declared performance			rmance Technical Specification				
See below per 1			ype		EN 310	Type tes	ting		
Bending properties	Туре	8mm	9mm	12mm	15mm	18mm	21mm	24mm	27mm
Bending strength	Fk, 0	35,6	33,2	28,5	26,3	32,4	26,8	28,1	24,1
(N/mm2)	Fk, 90	5,8	9,7	15,2	19,4	20,2	22,5	20,0	23,7

Place and date of issue	Issued by	Signature	
Ibaiti, 1st July 2013.	Bartolomeu da Silva Neto		
ibaiti, 1st July 2015.	Technical Director		



IBAITI MILL

CE Marking DoP No. SUI/PP/13/CE4

 ϵ

Product identification		PINE PLYWOOD EN 636-2 G						
	-							
Basic panel markings								
Product Types	8mm	9mm	12mm	15mm	18mm	21mm	24mm	27mm

CE

SUDATI - IBAITI

13

DoP No. SUI/PP/13/CE4

EN 13986:2004

Bond Class 3

E1

EN 636-2 G

XXmm

CE symbol

Manufacturing plant

Year of CE Marking

Declaratiom of Performance

Harmonized standard

Bond quality

Release of formaldehyde

Product identification

Product type

Place and date of issue	Issued by	Signature
Ibaiti, 1st July 2013.	Bartolomeu da Silva Neto	
ibaiti, 1st July 2013.	Technical Director	63



IBAITI MILL

REACH Statement DoP No. SUI/PP/13/CE4

C€

Product identification			PINE	PLYWOO	D EN 636	5-2 G			
Product Types	8mm	9mm	12mm	15mm	18mm	21mm	24mm	27mm	
Name and contact address	Indúst	ria de Cor	npensado	s Sudati L	.tda.				
of the manufacturer	Rod. B	Rod. BR 153, Km 04, s/n							
	Ibaiti,	Ibaiti, PR 84900-000 BRAZIL							
Mill identification	SUDAT	I - IBAITI							
In compliance to		REGULATION (EC) No 1907/2006							
	OF THE	OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL							
	of 18 D	of 18 December 2006 concerning the							
	Registr	Registration, Evaluation, Authorisation and Restriction of Chemicals							
	(REACH	(REACH)							
	Article	Article 33							
	Duty to	o commui	nicate info	ormation	on substa	ances in a	rticles		
And akowledging the	Candid	late List o	f Substan	ces of Ve	ry High Co	ncern fo	r Authoris	ation	
	(publis	hed in ac	cordance	with Artic	cle 59(10)	of the RE	ACH Regi	ulation)	
	Last up	dated: 20	0 June 20:	13 to cont	ain 144 s	ubstance	s.		
We hereby state that	-		•	ucer of th			•		
	The ab	ove ment	tioned pro	oduct is so	oftwood p	olywood r	nade sole	ly	
	of soft	of softwood veneers and bonded with phenol-formaldehyde resin,							
	and is	and is not treated with any chemicals.							
	The ab	The above mentioned product is an ARTICLE which do not contain							
	more t	more than 0.1% of any of the SUBSTANCES of the SVHC list.							
	NOTIFI	CATION is	s thus not	required	for this A	RTICLE.			

Place and date of issue	Issued by	Signature
Ibaiti, 1st July 2013.	Bartolomeu da Silva Neto	
ibaiti, 1st July 2013.	Technical Director	-63