

DECLARATION OF PERFORMANCE

0765 CPR 808, 3mm ≤ 40mm

1. Birch Plywood PF, unfaced, EN 636-2 S, 3mm ≤ 40mm

2. 3mm ≤ 40mm

3. Internal use as structural components in humid conditions

4. «Zheshartsky LPK» LTD
Gagarina Str. 1
169045 Zheshart
Ust-Vymsky district, Komi Republic
Russia
Tel: 8213447120
Fax: 8213447175
Email: zfk@zfk.ru; bte@zfk.ru

5. «Zheshartsky LPK» LTD
Gagarina Str. 1
169045 Zheshart
Ust-Vymsky district, Komi Republic
Russia
Tel: 8213447120
Fax: 8213447175
Email: zfk@zfk.ru; bte@zfk.ru

6. System 2+

7. Notified factory production control certification body Institute WKI № 0765 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

8. Declared performance

Essential characteristics	Performance	Harmonized technical specifications
Shear Strength limit over the glue line after boiling, MPa	Not less 1.0	EN 13986:2004 TY 5512-001-12886368-2014
Static bending strength limit along fibre dir. of outer layers, MPa	Not less 40	
Static bending strength limit across fibre dir. of outer layers, MPa	Not less 15	
Release of Formaldehyde	E1	
Reaction to fire	Class "E" (for thickness 3-8.9mm) D-s2,d0 (for thickness 9-40mm)	

Technical Control Chief **Safonova N.V.** /  10.01.2016 /
(Name and function) Signature date of signature

Zheshart, Komi Republic, Russia

